# Eskimo Ice

# For Serious Tournament Anglers



Crushed ice — preferred by fishermen, cools more quickly and packs better. Ice is produced continuously and pumped from a remote location to nearly any desired location whether it be to a fish box, drink box or coolers. Easy to install units are designed to be mounted below deck and protected from salt spray. Eskimo Ice Units can produce up to 600 pounds (272kg) of ice a day, up to 25 pounds (11.3kg) per hour, with discharge hose lengths up to 35 feet (10.6m) under normal operating conditions.

All self-contained and remote Eskimo Ice systems have Smart Logic Digital Displays. The system includes an automatic reset for key functions preventing owner from going to the machine space. The full menu of sensor and status lights monitor gas pressures, water level, ice clogs, ice levels, auger motor and compressor.

# Key Benefits

- Self-contained and remote models with digital controls
- Up to two remotely mounted digital displays/ user interface panels
- Pre-charged system
- Start time delay
- Sensors monitor all functions of system
- Includes water filter
- Manual reset to restart system from lock-out
- Improved fresh-water float switch
- Photo-electric ice level sensor
- Redesigned refrigerant meter for improved performance in cold water
- Optional covers for sides and top for protection and improved appearance



# Specification Details for Eskimo Ice Series


# Remote Models

Model	Remote Condensing Unit	Remote Auger Unit	Remote Condensing Unit	Remote Auger Unit	Remote Control
Voltage	115 volts AC	115 volts AC	230 volts AC	230 volts AC	
Frequency	60	60	60	60	
Running Amps	14	2	7	1	
Capacity		600 lb/day		600 lb/day	
Charge	26 oz	12 oz	26 oz	12 oz	
Water Consumption		72 g / day	72 g / day		
Dimensions (in/cm)					
Width	12.88 / 327	14.25 / 362	12.88 / 327	14.25 / 362	9.25 / 234
Depth	12.88 / 327	16.38 / 416.1	12.88 / 327	16.38 / 416.1	5.38 / 136
Height	15 / 381	20.88 / 530.4	15 / 381	20.88 / 530.4	6.38 / 162
Net Weight (lb/kg)	67 / 30.5	83 / 37.7	67 / 30.5	83 / 37.7	4 / 1.81

### Self-Contained Models

Model	Self-Contained	Self-Contained 230 volts AC	
Voltage	115 volts AC		
Frequency	60	60	
Running Amps	16	8	
Capacity	600 lb / day	600 lb / day	
Charge	14 oz	14 oz	
Water Consumption	72 g / day	72 g / day	
Dimensions (in/cm)			
Width	17.5 / 445	17.5 / 445	
Depth	23.5 / 597	23.5 / 597	
Height	22 / 559	22 / 559	
Weight (lb/kg)	135 / 61.4	135 / 61.4	

### Typical Remote Installation



The Eskimo Ice basic kit includes: Ice machine with condensate pan, 15' of ice delivery hose and insulation, electronic ice level control unit, and complete installation instructions.

### Typical Self-Contained Installation



## Remote System EIR600CD shown below



DOMETIC ENVIRONMENTAL CORPORATION
2000 N. Andrews Ave. Ext. | Pompano Beach, FL 33069 USA | 954-973-2477 | Fax 954-979-4414
P.O. Box 15299 | Richmond, VA 23227 USA | 804-746-1313 | Fax 804-746-7248 www.DometicEnviro.com | sales@DometicEnviro.com

United States & Canada Service Only:
8:00 AM to 5:00 PM Eastern Time | Marine Air AC Products: 954-973-2477 | Cruisair AC Products: 804-746-1313
24/7 A/C SERVICE HOTLINE: 5:00PM to 8:00 AM: 888-440-4494

International Sales & Service:
Europe & the Middle East: Call +44(0)870-330-6101 | For all other areas visit our website to find your nearest distributor.

Revised: 10-23-07 L-2450



