

Two Door Upright Refrigerators and Refrigerator/Freezers



RFU6800
and
RFU6200

Features

- 5 sizes to choose from; 6.0 cu.ft to 9.1 cu.ft (170 liters to 258 liters)
- Efficient 12/24 VDC Danfoss BD series compressor using environmentally friendly refrigerant R134a
- Efficient, quiet and reliable static condenser
- Adjustable low voltage protection to prevent complete battery discharge
- Rugged 18 gauge epoxy (coated satin coat) steel frame which is by far the strongest in the industry

- No spill ice cube tray
- Solid polyurethane foamed cabinets & doors
- Easy to clean polystyrene interior
- Galvanized steel outer cabinet shell
- Available in DC only, 12 & 24 VDC, or ACDC 12 & 24 VDC and 100-240 vac 50/60hz
- Fan standard
- All two door units run at 4.4 amps on 12VDC with the exception of the RFU9000 which has a running amperage of 5.5 amps
- RFU9000 is self venting!!!



RFU8000



RU7600



RFU9000

Model	Interior Volume		Freezer Volume		cut-out dimensions		Flange dimensions		Panel 1 size up to 1/4" thick		Panel 2 size up to 1/4" thick		Net weight lbs.	Standard Features	Available Options	
	cu ft	ltrs	cu ft	ltrs	in.	mm	in.	mm	in.	mm	in.	mm				
RU7600	7	198	2x0.40*	2x11.3*	H	57 3/4	1467	58 3/4	1493	28	711	28	711	96		
					W	20 1/4	515	21	533	19 5/8	499	19 5/8	499			
					D	18 1/2	470									
RFU6200	6	170	2.5	71	H	47 3/4	1204	48 3/4	1229	28	711	17 5/16	440	93		
					W	20 1/4	515	21	533	19 5/8	499	20 3/16	513			
					D	20 1/2	521									
RFU6800	6.8	193	2.5	71	H	47 3/4	1204	48 3/4	1229	28	711	17 5/16	440	95		
					W	20 1/4	515	21	533	19 5/8	499	20 3/16	513			
					D	21 1/2	547									
RFU8000	6.8	193	2.5	71	H	52 7/8	1343	53 3/8	1356	28	711	17 5/16	440	100		
					W	23 1/4	591	24 5/16	618	19 5/8	499	19 5/8	499			
					D	23 1/2	597									
RFU9000	9.1	258	2.6	74	H	52 7/8	1343	53 1/4	1353	29 5/8	752	13 3/8	340	100		
					W	23 1/4	591	24 3/4	629	21 3/8	543	21 3/8	543			
					D	22 3/4	578									

* Note: Special order available without freezer compartments on RU7600 only